



ASI1201E/ASI1201E-D

Water-proof RFID Standalone



Features

- Support 30,000 valid cards & 150,000 records
- Support multiple cards(default IC card) (“-D” means ID EM card)
- Support card, password and combination
- TCP/IP to PC
- Wiegand or RS-485 interface to reader
- Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- Anti-passback, multi-card open
- Water-proof design
- Support 128 efficient time and holiday schedules
- Watch dog function ensure device free from halting



Technical Specification

| | | |
|---------------------------|---|------------|
| Mode | ASI1201E | ASI1201E-D |
| System | | |
| Main Processor | 32 Bit | |
| Memory | 16M | |
| Input/Output Ports | | |
| Input | Door sensor x 1, Exit button x 1 | |
| Output | Relay x 1 (Door lock,) | |
| Reader | Reader x 1 | |
| Card Read | | |
| Read Format | 13.56MHz | 125KHz |
| Read Range | 1-2cm (max.) | |
| Response Time | <0.1s | |
| Capacity | | |
| Cardholders | 30,000 | |
| Events | 150,000 | |
| Function | | |
| User Management | General, VIP, Guest, Patrol, Black list, Duress | |
| Alarm Function | Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm | |
| Period Setting | Support 128 groups of schedule, 128 groups of periods and 128 groups of holiday periods | |

Interface

| | |
|-----------|----------------|
| To PC | RJ45(10/100M) |
| To Reader | Wiegand/ RS485 |



General

| | |
|-----------------------|--|
| RTC | Yes |
| Voice Prompt | No |
| Beep Tone | Buzzer |
| Keyboard | Sensitive touch keypad with blue backlight |
| Power Supply | 9-15DC/200mA |
| Operating Temperature | -30°C to +60°C |
| Working Humidity | ≤95% |
| Dimension(W×D×H) | 62mm×23mm×142mm |
| Weight | 0.5kg |
| Working Environment | Indoor |

Certificates

| | |
|-----|-----|
| CE | Yes |
| FCC | Yes |

Dimensions



Application

Small Office
One door controller

